

DUCATI

Panigale V4 1100 my 18/23

product	code	description
Steering damper kit	SD.D124K	SDK (stock)
Steering damper kit	SD.D124R	SDR (stock)
Monoshock (C-R-L-P)	MD137.15K	M46K standard
Monoshock (C-R-L-HP)	MD137.15IS	M46K+IS hydraulic spring preload
Monoshock (CH-CL-R-L-HP)	MD137.15R	M46R Racing (IS preload unit)
Fork kit (type Showa BPF)	FD136RK-BP1	FRK Hydraulic kit (step1)
Fork kit (type Showa BPF)	FD136RK-BP2	FRK Hydraulic kit (step2)
Fork kit (C-R-P) (type Showa BPF)	F25D136R	F25R Hydraulic Cartridge kit
Fork kit (C-R-P) (type Showa BPF)	F25D136SA	F25SA Sealed Hydraulic Cartridge kit



M46R



High speed
Low speed
Compression
adjustment
+ -

Hydraulic
spring
preload unit
+ -

Rebound
adjustment
+ -

Length
adjustment
+ -



M46K-IS

Dark Series on demand



SD-R



SD-K



CH = HighSpeed Comp. adj. / regolazione Compressione AV
CL = LowSpeed Comp. adj. / regolazione Compressione BV
C = Compression adj. / regolazione Compressione
R = Rebound adj. / regolazione Estensione
L = Length adj. / regolazione Interasse
P = spring Preload / Precarico molla
HP = hydraulic spring Preload adj. / Precarico molla idraulico.

DUCATI

Panigale V4 1100 my 18/23



F25SA Sealed cartridge asymmetric system



Rebound unit
(range: 38 clicks)

Preload unit
(range: 15 mm)

Compression unit
(range: 38 clicks)



FRK-BP1



FRK-BP2

F25R Quad-valve asymmetric system



on demand
the technopolymer fork cap tools

T21 fork cap tool 36 (8 sides)



T22 fork cap tool 28 (6 sides)

Rebound unit
(range: 38 clicks)

Preload unit
(range: 15 mm)

Compression unit
(range: 38 clicks)